

DUETTO High Output DIRECT

Housing: Aluminium profile with integrated opal diffuser
Design: SATTLER



921 mm 36.2" 1255 mm 49.4" 1574 mm 61.9"	1924 mm 75.7"	2306 mm 90.8"	2609 mm 102.7 3516 mm 138.4"
1 part 4 cables	1 part 6 cables	2 parts 6 cables	3 parts 6 cables

Sizes	Size: Ø mm	Inches	LED Watt	Lumen ¹⁾	Weight ²⁾ kg/lbs		Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
	921 mm	36.2"	88	5.544	7,0	15.4	2090.	X X.	X X.	X X.	X X.	X X X.	X
	1255 mm	49.4"	118	7.606	9,5	20.9	2091.	X X.	X X.	X X.	X X.	X X X.	X
	1574 mm	61.9"	148	9.699	13,0	28.6	2092.	X X.	X X.	X X.	X X.	X X X.	X
	1924 mm	75.7"	181	11.805	13,5	29.7	2093.	X X.	X X.	X X.	X X.	X X X.	X
	2306 mm	90.8"	217	14.403	17,0	37.4	2094.	X X.	X X.	X X.	X X.	X X X.	X
	2609 mm	102.7"	245	16.628	18,5	40.7	2095.	X X.	X X.	X X.	X X.	X X X.	X
	3516 mm	138.4"	331	21.043	23,0	50.7	2096.	X X.	X X.	X X.	X X.	X X X.	X

LED	Standard:	Warm-white	3000 K	X X X X.	30.	X X.	X X.	X X.	X X X.	X
CRI > 90 Mac Adam 3 SELV L80 B10 50.000 h	Optional:	Neutral-white	4000 K	X X X X.	40.	X X.	X X.	X X.	X X X.	X
		Extra warm-white	2700 K	X X X X.	27.	X X.	X X.	X X.	X X X.	X

Dimming	Standard:	Without Dimmer	X X X X.	X X.	01.	00.	X X.	X X X.	X
	Optional:	0 - 10 V	X X X X.	X X.	51.	00.	X X.	X X X.	X
		DALI	X X X X.	X X.	61.	00.	X X.	X X X.	X
		CASAMBI	X X X X.	X X.	81.	00.	X X.	X X X.	X

Finishes	Standard:	12 white, similar RAL 9003	Optional:	10 black fine textured	X X X.	X X.	X X.	X X.	X X X.	X

Power supply cable	Standard:	Z 70 Silver	X X X.	X X.	X X.	X X.	X X.	Z70.	X


DUETTO High Output DIRECT

Housing: Aluminium profile with integrated opal diffuser
Design: SATTLER




921 mm 36.2" 1255 mm 49.4" 1574 mm 61.9"	1924 mm 75.7"	2306 mm 90.8"	2609 mm 102.7" 3516 mm 138.4"
1 part 4 cables	1 part 6 cables	2 parts 6 cables	3 parts 6 cables


Mounting version




up to Ø 1574 mm / 61.9"
4-point suspension
up to Ø 3516 mm / 138.4"
6-point suspension
with external power supply
unit in suspended ceiling



up to Ø 1574 mm / 61.0"
4-point suspension
up to Ø 3516 mm / 138.4"
6-point suspension
with external power supply
unit in separate canopy



up to Ø 1924 mm / 75.7"
suspension through canopy



up to Ø 1924 mm / 75.7"
suspension with pendant
canopy and steel cables
(a) 5000 mm / 196.8" +
(b) 3000 mm / 118.1"

Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
X X X.	X X.	X X.	X X.	X X.	X X X.	-

A, B = Distance of external power supply unit to light fixture max. 10m / 394".

E, S = Minimum suspension height is half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 3000mm/118" and/or power supply cable 3000mm/118" version S 5000 + 3000mm / 197" + 118"



---	---	---	---	---	---	---
-----	-----	-----	-----	-----	-----	-----

Complete order number

Power supply units:		Type / Size mm / inch L x W x H	For use with Mounting version	Protective rating
	DE 1F	363 x 143 x 56 mm / 14.2 x 5.6 x 2.2"	A (up to Ø 1255 mm)	IP 20
	DE 2F	363 x 283 x 56 mm / 14.2 x 11.1 x 2.2"	A (up to Ø 2609 mm)	IP 20
	DE 3F	363 x 403 x 85 mm / 14.2 x 15.7 x 3.3"	A (up to Ø 3516 mm)	IP 20

Further sizes on request

Canopy:		Type/ Size mm / inch Ø cover plate / body / H	For use with Mounting version	Protective rating
	DB 350	Ø 350 / 320 / 60 mm / 13.7 x 12.5 / 2.3"	B, E (up to Ø 1924 mm)	IP 20
	DB 510	Ø 510 / 470 / 60 mm / 20.0 x 18.5 / 2.3"	B (up to Ø 3516 mm)	IP 20
	PB 375	Ø 90 H 375 mm / 3.5 x 14.8"	S (Ø 921 mm)	IP 20
	PB 652	Ø 90 H 652 mm / 3.5 x 25.7"	S (up to Ø 1924 mm)	IP 20

Colour: 12 white, similar RAL 9003, contact factory for other finishes
USA/Canada: Canopy mounts to 4" octagonal junction box.

Input voltage for all external power supply units and canopy is 100-240 VAC 50-60 Hz

Optional




CASAMBI wall-switch

207. 00. 00. 00. 12. (white)

207. 00. 00. 00. 10. (black)

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch may be also used on its own as it is attached to the wall plate using magnets.



Power cable cover plate for mounting version A

200. 00. 00. 00. 12. (white)

Consisting of a cavity ceiling box with 80mm round metal cover. Applicable to mounting version A.

