


## DUETTO High Output DIRECT / INDIRECT

Housing: Aluminium profile with integrated opal diffuser  
Design: SATTLER



921 mm 36.2" 1255 mm 49.4" 1574 mm 61.9"	1924 mm 75.7"	2306 mm 90.8"	2609 mm 102.7" 3516 mm 138.4"
1 part 4 cables	1 part 6 cables	2 parts 6 cables	3 parts 6 cables

Sizes	Size: L x W x H mm	Inches	LED Watt direct/indirect	Lumen <sup>1)</sup> direct/indirect	Weight <sup>2)</sup> kg/lbs	Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
	Ø 921 mm	36.2"	88 / 16	5.544 / 787	7,0 15.4	2090.	XX.	XX.	XX.	XX.	XXX.	X
	Ø 1255 mm	49.4"	118 / 22	7.606 / 1.135	9,5 20.9	2091.	XX.	XX.	XX.	XX.	XXX.	X
	Ø 1574 mm	61.9"	148 / 28	9.699 / 1.430	13,0 28.6	2092.	XX.	XX.	XX.	XX.	XXX.	X
	Ø 1924 mm	75.7"	181 / 35	11.805 / 1.768	13,5 29.7	2093.	XX.	XX.	XX.	XX.	XXX.	X
	Ø 2306 mm	90.8"	217 / 42	14.403 / 2.139	17,0 37.4	2094..	XX.	XX.	XX.	XX.	XXX.	X
	Ø 2609 mm	102.7"	245 / 48	16.628 / 2.387	18,5 40.7	2095..	XX.	XX.	XX.	XX.	XXX.	X
	Ø 3516 mm	138.4"	331 / 65	21.043 / 3.127	23,0 50.7	2096.	XX.	XX.	XX.	XX.	XXX.	X
<b>LED</b>	Standard: Warm-white Optional: Neutral-white Extra warm-white Direct and indirect light are switchable and dimmable together only.	3000 K 4000 K 2700 K	XXXX. XXXX. XXXX.	30. 40. 27.	XX. XX. XX.	30. 40. 27.	XX. XX. XX.	XX. XX. XX.	XXX. XXX. XXX.	X X X		
<b>Dimming</b>	Standard: Without Dimmer Optional: 0 - 10 V DALI CASAMBI	Without Dimmer 0 - 10 V DALI CASAMBI	XXXX. XXXX. XXXX.	XX. XX. XX.	02. 52. 62. 82.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XXX. XXX. XXX.	X X X	
<b>Finishes</b>	Standard:  12 white, similar RAL 9003 Optional:  10 black fine textured	12 white, similar RAL 9003 10 black fine textured	XXX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XXX. XXX. XXX.	X X X		
<b>Power supply cable</b>	Z 70 Silver	Z 70 Silver	XXX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XXX. XX. XX.	XX. XX. XX.	XX. XX. XX.	XX. XX. XX.	Z70. Z70. Z70.	X X X	




## DUETTO High Output DIRECT / INDIRECT

Housing: Aluminium profile with integrated opal diffuser  
Design: SATTLER




921 mm 36.2" 1255 mm 49.4" 1574 mm 61.9"	1924 mm 75.7"	2306 mm 90.8"	2609 mm 102.7" 3516 mm 138.4"
1 part 4 cables	1 part 6 cables	2 parts 6 cables	3 parts 6 cables


### Mounting version




up to Ø 1574 mm / 61.9"  
4-point suspension  
up to Ø 3516 mm / 138.4"  
6-point suspension  
with external power supply  
unit in suspended ceiling



up to Ø 1574 mm / 61.0"  
4-point suspension  
up to Ø 3516 mm / 138.4"  
6-point suspension  
with external power supply  
unit in separate canopy



up to Ø 1924 mm / 75.7"  
suspension through canopy



up to Ø 1574 mm / 61.0"  
suspension with pendant  
canopy and steel cables  
(a) 5000 mm / 196.8" +  
(b) 3000 mm / 118.1"

Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
X X X.	X X.	X X.	X X.	X X.	X X X	<input type="checkbox"/>

A, B = Distance of external power supply unit to light fixture max. 10m / 394".

E, S = Minimum suspension height is half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 3000mm/118" and/or power supply cable 3000mm/118" version S 5000 + 3000mm / 197" + 118"

Complete order number

---	---	---	---	---	---	---
-----	-----	-----	-----	-----	-----	-----

Power supply units:		Type / Size mm / inch L x W x H	For use with Mounting version	Protective rating
	DE 1F	363 x 143 x 56 mm / 14.2 x 5.6 x 2.2"	A (Ø 921 mm)	IP 20
	DE 2F	363 x 283 x 56 mm / 14.2 x 11.1 x 2.2"	A (up to Ø 1574 mm)	IP 20
	DE 3F	363 x 403 x 85 mm / 14.2 x 15.7 x 3.3"	A (up to Ø 3516 mm)	IP 20

Further sizes on request

Canopy:		Type/ Size mm / inch Ø cover plate / body / H	For use with Mounting version	Protective rating
	DB 350	Ø 350 / 320 / 60 mm / 13.7 x 12.5 / 2.3"	B, E (up to Ø 1574 mm)	IP 20
	DB 510	Ø 510 / 470 / 60 mm / 13.7 x 12.5 / 2.3"	B (up to Ø 3516 mm)	IP 20
	PB 375	Ø 90 H 375 mm / 3.5 x 14.8"	S (Ø 921 mm)	IP 20
	PB 652	Ø 90 H 652 mm / 3.5 x 25.7"	S (Ø 1574 mm)	IP 20

Colour: 12 white, similar RAL 9003, contact factory for other finishes  
USA/Canada: Canopy mounts to 4" octagonal junction box.

Input voltage for all external power supply units and canopy is 100-240 VAC 50-60 Hz

### Optional




CASAMBI wall-switch

207. 00. 00. 00. 12. (white)

207. 00. 00. 00. 10. (black)

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch may be also used on its own as it is attached to the wall plate using magnets.



Power cable cover plate for mounting version A

200. 00. 00. 00. 12. (white)

Consisting of a cavity ceiling box with 80mm round metal cover. Applicable to mounting version A.

