SATTLER

FINO			Но	using:			cture with f		t head and	metal s	tand				
FLOOR				sign:			Michael Sch	-							
180° Titabe	/			round Ø 2	2mm / 0.9"	240 mm 9.4" Ø 200 mn 7.8"		H 1300 mm 51.2"							
	Size: Ø / H mm		Inches	LEC	D Watt Lu	umen ¹⁾	Weight ²⁾ kg/ l	bs	Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
Sizes	Ø22/H1300 n	nm	Ø0.9/H	51.2"	4 3	313	2,5 / 5.5	5	1537.	Х Х.	ΧХ.	х х.	Х Х.	X X X.	х
LED	(LED) S	tandard:	Warm-wh	iite		3000 K			XXX.	30.	Х Х.	х х.	ΧХ.	ХХХ.	х
CRI > 90 Mac Adam 3 SELV L80 B10 100.000 h		ptional:	Neutral-w Extra war			4000 K 2700 K			x x x. x x x.	40. 27.	x x. x x.	x x. x x.	x x. x x.	x x x. x x x.	x x
Dimming	C		Push butt	on for dimn	ning				xxx.	х х.	07.	00.	х х.	x x x.	х
Finish Standard:	66 c bronze anodised brushed	Optional:	60 silver anodised brushed	62 black anodised brushed	65 champ. gold anodised brushed	d			X X X.	х х.	х х.	х х.		x x x.	х
Power supply cable	Z 80 Black								x x x.	x x.	х х.	х х.	x x.	Z80.	x
Mounting version	pluggat	ole on the lamp		nt including on cable (bla ry-specific plug	ack) with p		dapter		xxx.	х х.	х х.	x x.	х х.	x x x.	N
			Stand san as selecte	ne colour d finish					1537. Complete c		07. nber	00.		Z80.	N
			Input vo is 220-	Input voltage for all external power supply units and canopy is 220-240 VAC 50-60 Hz											
Germa	rafted in ny, ed quality		IP 2	0 Protective of luminain	rating re		Direct light distribution		Protection c only suitable voltage sup	e for very lo	w	F	on ordina which hav	es are suitable f ry flammable r ve an inflamma 00° C. / 392° F.	naterials,

www.sattler-lighting.com

FINO FLOOR

5.4.23

Technical data is subject to change. Errors and omissions excepted 1) Net lumen output: Losses due to diffusers and reflectors are considered. Lumen values refer to an ambient temperature of max. 35° C. / 95° F. 2) Weight of lights without remote technical unit or canopy.